


GF4.5 Standard-Set steel reel Ø 330 mm


for fiberglass rod Ø 4,5 mm, incl. double run-out system

Item no.: **20002**








VIDEO




GF4.5

Click here Video 

Click here
Productioninformation 




Detailed image




Lateral parking brake and double run-out system (quick outlet and automatic run-out brake)

Quick run with rollers



Automatic run-out brake



DATA	
ITEM NO.	20002
WEIGHT	3,28 kg
DIMENSION	L 365 mm x B 250 mm x H 435 mm
BASKET Ø	330 mm
MATERIAL	CDP / Powder coated
EAN-CODE	9120045473711

- ADVANTAGES**
- Spare part for Fiberglass rods Ø 4.5 mm
 - Double run-out system with quick outlet and run-out stop stop
 - CDP/powder-coated
 - 2 x threaded bolts to „stow“ various guide heads

DESCRIPTION

The GF4.5 steel reel standard set Ø 330 mm is ideal for fiberglass rods Ø 3 mm or 4.5 mm. The double release system with quick release or release stop ensures full control, while the automatic release brake ensures safety. The KTL-coated frame and powder-coated basket make the reel particularly robust and durable. Two threaded bolts allow for practical storage of guide heads.


Scope of supply: 1 x Standard-set steel reel Ø 330 mm with double run-out system, parking brake, incl. 2 x threaded bolts

INFORMATION

Suitable products:

GF4.5 Replacement fiberglass rod

- 30 m - Item no. 20311
- 40 m - Item no. 20312
- 50 m - Item no. 20313
- 60 m - Item no. 20314
- 80 m - Item no. 20315



Click here
Productioninformation 