

**RP5 - 30 m + GF4.5 Profi-Set** Fiberglass rod Ø 4,5 mm - 60 m

Promotion Cable pulling tool + Fiberglass rod

Item no.: 11120



**VIDEO**

RP5

[Click here Video](#)

**VIDEO**

GF4.5

[Click here Video](#)

[Click here Productinformation](#)

Description GF4.5 Profi-Set see page 2

Very narrow bending radius

$R = 15 \text{ mm}$

Virtually break-free even with tightest radii

50 % less friction resistance

Only punctual contact

Total breaking load 270 kg

Strand + Pressing + Guiding head + Eyelet

**DATA**

ITEM NO.:	<b>11120</b>
LENGTH	30 m + 60 m
WEIGHT	7,09 kg
DIMENSION	L 360 x B 250 x H 475 mm
MATERIAL	RP5 - Special plastic GF4.5 Fiberglass core with PP sheath
EAN-CODE	9120045473353

**BESCHREIBUNG**

The **RP5 - RUNPOTEC Polyester Ø 5.5 mm** is a cable pulling tool without a meter counter. The triple-twisted special plastic tape Ø 5.5 mm has an even better thrust effect than the glass fiber rod Ø 3 mm, and the frictional resistance is only half as high due to its point contact. The patented RG7 guiding head with swivel compensation Ø 5.5 mm (pressed at the beginning and end of the tape) enables the tightest radii to be overcome (bending radius 15 mm). The RP5 is stored in a storage box suitable for construction sites, including a glide back protection (only stops the RG7 guiding head). Total breaking load 270 kg. Laborious and time-consuming repair work is no longer necessary, as the cable pulling system is virtually break-proof.

**Optimal area of application:** for pipe inner diameters of 9 mm - 32 mm.

**GF4.5 Glass fiber rod Ø 4.5 mm - Profi set - 60 meters - RUNPOTEC thread RTG Ø 6 mm** with robust steel reel Ø 330 mm (KTL/powder-coated) with new double outlet system (automatic outlet brake and quick outlet), additional locking brake, extendable feet, and storage compartment for accessories. Glass fiber rod total breaking load 1300 kg, total breaking load 220 kg.

**Optimal application area:** for pipe diameters 30 mm - 80 mm.

**Scope of supply:** 1 x RP5 in plastic box, Length: 30 m, GF4.5 Profi-Set fiberglass rod Ø 4,5 mm, Length: 60 m

**VORTEILE**

- 50% less frictional resistance
- 270 kg Total breaking load RP5
- 2 x RG7 RUNPOGLIDER with swivel
- incl. steel reel
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 1300 kg
- Total breaking load 220 kg
- Bending radius 120 mm

**INFORMATION****Compatible accessories****RP5 Replacement fish tape**

20 m – Item no.: 20240

30 m – Item no.: 20241

[Click here Productinformation](#)**Cable pulling loop with hook (Quick release fastener) – Set of 4**

Item no.: 10159

[Click here Productinformation](#)

### GF4.5 Profi-Set fiberglass rod Ø 4,5 mm

for pipe diameter 30 - 80 mm, incl. double run-out system

Item no.: 10052 | 10055 | 10057 | 10047 | 10050



**Ergonomic holding and carrying handle**

**Lateral parking brake**

**RG7 - Guiding head with front thread and eyelet incl. swivel**

**Double run-out system, quick outlet and automatic run-out brake**

**Extendable standing feet and storage compartment incl. accessories**

**Attention!** Electrical conductive

**Beginning:** RG7 - Guiding head incl. swivel Ø 7 mm, thread RTG Ø 6 mm, screwed onto strand

**Ending:** Ending joint, stainless steel, thread RTG Ø 6 mm

**Detailed image**

extendable standing feet

**Lateral parking brake and double run-out systems (Quick outlet and automatic run-out brake)**

Quick run with rollers      Automatic run-out brake

[Click here VIDEO](#)

GF4.5

[Click here Video](#)

**KG 220**

[Click here Productinformation](#)

Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
4,5 mm	30 - 80 mm	120 mm	55 mm	1300 kg	220 kg

DATA					
ITEM NO.	10052	10055	10057	10047	10050
LENGTH	30 m	40 m	50 m	60 m	80 m
WEIGHT	4,84 kg	5,08 kg	5,32 kg	5,56 kg	6,04 kg
MATERIAL ROD	Fiberglass core with PP sheath				
BENDING RADIUS	120 mm				
PIPE Ø	optimal from 30 - 80 mm				
DIMENSION	H: 365 x B 260 x H 454 mm				
TOTAL BREAKING LOAD	220 kg				

#### DESCRIPTION

GF4.5 fiberglass rod (duct rodders) Ø 4,5 mm Profi-Set - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (CDP/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Fiberglass rod breaking load 1300 kg, total breaking load 220 kg.

**Optimal field of application:** for pipe diameters 30 mm - 80 mm.

**Application video:** a short, very informative application video can be viewed by scanning the QR code or on [www.RUNPOTEC.com](http://www.RUNPOTEC.com).

**Scope of supply:** 1 x GF4.5 fiberglass rod Ø 4,5 mm Profi-Set, stainless steel ending joint on both sides (start/end), 1 x steel reel Ø 330 mm incl. double run-out system, extendable feet and storage compartment, additional accessories: 1 x RG7 RUNPOGLIDER with thread and swivel, 2 x ending joint, 1 x coupling joint, 1 x shackle, 1 x special glue, 1 x roller

#### ADVANTAGES

- incl. steel reel Ø 330 mm
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 1300 kg
- Total breaking load 220 kg
- Bending radius with ending joint 120 mm
- Bending radius only rod 55 mm

#### INFORMATION

Compatible with:

**RC2 Inspection camera**  
30 m - Item no.: 10140  
50 m - Item no.: 10141

[Click here Productinformation](#)

**RC3 Inspection camera (digital)**  
15 m - Item no. 10214

[Click here Productinformation](#)