

**CAMERA HEAD** Ø 3,9 mm flexible - 1 m

for RC2 Inspection camera

Item no.: **20488**



DATA	
ITEM NO.	<b>20488</b>
WEIGHT KG	0,053 kg
DIMENSION	H 20 mm x DM 205 mm
CAMERA HEAD	100.000 Pixel (320 x 240)
LIGHTNING	2 x LED (dimmmable)
PROTECTION CLASS	IP 67
ANGLE VIEW	54 °
DIAMETER	3,9 mm
EAN-CODE	9120045474961

**ADVANTAGES**

- Pipe inspection from Ø 4 mm
- Protection class IP67
- Suitable for RC2 inspection camera
- Angle of view 54°

**DESCRIPTION**

Flexible camera head Ø 3.9 mm (extra slim) for RC2 inspection camera - length 1 m  
 Resolution: 100,000 pixels (320 x 240), protection class - IP 67, image angle - 54 degrees, 2 x LED adjustable in 6 steps, autofocus.

**Optimal area of application:** ideal for short distances with flexible goose-neck. For cavity wall, plant, machine, engine, ventilation, control, or inspection purposes. Inaccessible cavities, tight angles, shafts, ducts, small passages, and many other applications.

**Scope of supply:** 1 x Camera probe Ø 3,9 mm flexible - length: 1 m

**INFORMATION**

Compatible with:

**RC2 Inspection camera**

30 m - Item no.: 10140

50 m - Item no.: 10141



Click here Productinformation