


ROLLER Ø 24 mm

for RUNPOTEC products with thread RTG Ø 6 mm

Item no.: **20279****DATA**

ITEM NO.	20279
WEIGHT	0,027 kg
DIMENSION	Ø 24 mm
THREAD	RTG Ø 6 mm
MATERIAL	Aluminum/ Stainless steel
EAN-CODE	9120045473230

DESCRIPTION

The high-quality roller ensures significantly improved sliding and rolling in empty conduits and makes it easier to pull cables through. It is compatible with fiber optic rods with a diameter of 4.5 mm and 6 mm as well as with RUNPOSTICKS. Thanks to the RUNPOTEC thread RTG Ø 6 mm, it is easy to install and efficient to use. Made of aluminum and stainless steel, it is durable and resistant.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x Roller Ø 24 mm with thread RTG Ø 6 mm

ADVANTAGES

- Substantially improved gliding or rolling in empty pipes
- RUNPOTEC RTG Ø 6 mm thread
- Aluminium/stainless steel

INFORMATION

Compatible with:

**GF4.5 Fiberglass rod
Profi-Set or Standard-Set**

Length 30 - 80 m

[Click here
Produktinformation](#)



**GF6 Fiberglass rod
Profi-Set or Standard-Set**

Length 40 - 80 m

[Click here
Produktinformation](#)

