

Cable lubricant

Item	PU	Item no.	Rec. trade price
	1 8	30064 21157	8,90 € 71,20 € 63,60 €
Cable lubricant GEL – 1000 g Reduces friction, non-corrosive, skin-friendly, temperature-resistant up to 85 °C/185°F NON-FLAMMABLE			
Info: Unit price € 7.95 at a PU of 8 pcs.			
	1 24	30467 21156	4,40 € 105,60 € 93,60 €
Cable lubricant GEL – 250 g Reduces friction, non-corrosive, skin-friendly, temperature-resistant up to 85 °C/185°F NON-FLAMMABLE			
Info: Unit price € 3.90 at a PU of 24 pcs.			
	1 12	20523 21158	8,20 € 98,20 € 87,60 €
Cable lubricant SPRAY – 400 ml Special attachment – spray large areas or use the flip-up tube for precise application. Excellent sliding and lubricating properties, does not dry out, colorless, odorless NON-FLAMMABLE			
Info: Unit price € 7.30 at a PU of 12 pcs.			
	1 12	20522 21155	7,10 € 85,20 € 75,60 €
Cable lubricant FOAM – 400 ml Special attachment – spray large areas or use the flip-up tube for precise application. Excellent sliding and lubricating properties, does not dry out, water-soluble NON-FLAMMABLE			
Info: Unit price € 6.30 at a PU of 12 pcs.			
	1	30063	7,40 €
Cable lubricant LIQUID – 1000 ml Significantly reduces friction, economical in use, water-soluble, biodegradable, non-sticky, colorless and odorless			

Product properties	GEL – 1000 g	GEL – 250 g	SPRAY – 400 ml	FOAM – 400 ml
Long-lasting lubricating effect	● ● ●	● ● ●	● ● ●	● ● ●
Dissolves without residue	● ● ●	● ● ●	● ● ●	● ● ●
Non-stick	● ● ●	● ● ●	● ● ●	● ● ●
Low consumption	● ●	● ●	● ● ●	● ● ●
Pipe diameter / 0 – 40 mm	● ● ●	● ● ●	● ● ●	● ● ●
Pipe diameter / 40 – 500 mm	● ● ●	● ●	● ●	● ●
Biodegradable (in %)	100 %	100 %	–	92 %
VOC free (Volatile Organic Compounds)	Yes	Yes	No	Yes
Dosage	Opening 3 – 12 mm	Opening 2 – 8 mm	Spray head with folding tube	Spray head with folding tube
May cause stains (depending on the surface)	Rare	Rare	Medium	Low
Working temperature	1°C to 50°C	1°C to 50°C	-10°C to 50°C	-10°C to 50°C
Risk of short circuit	⚠ ⚠	⚠ ⚠	⚠	⚠
Drop formation during overhead work	💧 💧	💧 💧	💧 💧 💧	💧
Application examples				